



***GASBLASTER EPRO-8***

**BACTERIA & ODOR ABATEMENT SYSTEM**

- All stainless steel Construction
- Automatic, versatile & portable
- Low power consumption
- Hour meter / On off indicator light
- Destroys Odors- Not a Cover Up
- Economical to Use
- Low Maintenance
- No costly chemicals
- Leaves no residue



**Commercial**

Dumpsters  
 Food Processing  
 Restaurants  
 Hotels  
 Nursing Homes  
 Recycle Centers  
 Fast Food  
 Supermarkets  
 Laundries

**Municipal Treatment**

Aeration Basins  
 Holding Tanks  
 Dewatering Facilities  
 Clarifiers Sludge  
 Dryers  
 Compost Facilities  
 Anaerobic Digesters  
 Lift Stations  
 Municipal Wastewater  
 Plants (WWTP)

**Industrial Treatment**

Chemical Processing  
 Pharmaceutical  
 Fermentations  
 Coating Processes  
 Storage Tanks  
 Fish & Poultry  
 Pulp & Paper  
 Animal Rendering  
 Paint Stripping  
 Breweries

**WILL DESTROY, NOT JUST COVER-UP, THE FOLLOWING AIRBORNE ODOR CAUSING SUBSTANCES:**

Hydrogen Sulfide (H<sub>2</sub>S), Alcohols, Ketones, Aldehydes, Acetic Acid, Creosols, Dimethydisulfide, Ammonia, Amines, Chlorine, Phenols, Acrylates, Mercaptans, Carboxylic Acids, Sketoles, Sulfur Dioxide (SO<sub>2</sub>) and Butyric Acid.

**Specifications**

<b>MODEL :</b>	<b>EPRO-8</b>
<b>VOLTAGE:</b>	110V 2 AMPS fused 50/60 HZ
<b>WEIGHT:</b>	25 LBS.
<b>MATERIAL:</b>	STAINLESS STEEL
<b>DIMENSIONS:</b>	11" x 15" x 12"
<b>OZONE OUTPUT:</b>	<b>500 to 8000 mg/h adjustable</b>
<b>CONTROLS:</b>	ON/OFF/HOLD or timed from 15 min. to 12 hours
<b>COVERAGE:</b>	Up to 10,000 sq. ft. for odors, 2000 sq. ft. for mold or high H <sub>2</sub> S
<b>OPTIONS:</b>	3" or 4" input and output spouts for duct tubing connections
<b>WARRANTY:</b>	The EPRO-8 is warranted against defects in materials and workmanship for a period of 1 year from date of shipment.

***Producing Solutions***